

# UT-5564A

UT-5564A  
-10V~+10V                      0 ~ 20mA                      D/A                      !  
Modbus RTU  
RS-485  
115200 bps

¥                      &  
¥                      Modbus-RTU                      03 06 16  
¥                      1200/2400/4800/9600/19200/38400/57600/115200 bps  
¥                      # \* @ 1 / 1 \* 7 1  
¥                      1~247  
¥                      RS485  
¥                      -10V~+10V  
¥                      0 ~ 20mA  
¥                      ± 0.5% of FSR  
¥                      1K<sup>1</sup>                      24V DC  
¥                      3000V DC  
¥                      +12 ~ +30V DC  
¥                      2.5W  
¥                      -40° C ~ +85° C  
¥                      -40° C ~ +85° C  
¥                      5% ~ 95%RH

4.1



## 4.2

(R)+Vs		Iout3	%
(B)GND		Vout0	"
(G)DATA-	RS-485-B	Vout1	#
(Y)DATA+	RS-485-A	Vout2	\$
Iout0	"	Vout3	%
Iout1	#	AGND	
Iout2	\$	AGND	

## 4.3

PWR:

TXD

RXD

UT-5564A

Modbus-RTU

03 06 16

Modbus-RTU

Modbus

## 6.1



	01
	9600bps
	1 * @ 1
0	0V 0mA
1	0V 0mA
2	0V 0mA
3	0V 0mA